

DECLARATION OF PERFORMANCE

No: TR26WWM

1. Unique identification code of the product-type:

TR26WWM, Machine graded structural timber with rectangular cross-section, Whitewood (PCAB), M TR26, dimensions: thickness 31-100 mm, width 60-275 mm

2. Intended uses:

Graded structural timber with rectangular cross-section for construction works

3. Manufacturer:

Versowood Oy, Teollisuustie 60, FIN-19110 VIERUMÄKI, www.versowood.fi

5. System of AVCP:

System 2+

6a. Harmonised standard:

EN 14081:2010+A1:2011

Notified body:

Notified factory production control certification body Inspecta Sertifiointi Oy (0416) performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control and issued the certificates of conformity of the factories production control 0416-CPR-5381 (Vierumäki unit), 0416-CPR-5379 (Riihimäki unit), 0416-CPR-5573 (Otava unit) and 0416-CPR-4781 (Hankasalmi unit)

7. Declared performances

| Essential characteristics | Performance TR26 | Harmonised technical specification |
|-------------------------------------|------------------------|------------------------------------|
| Bending | 28,3 N/mm ² | |
| Compression parallel | 22,5 N/mm ² | |
| Tension parallel | 17 N/mm² | |
| Shear | 4 N/mm ² | EN 14081:2010+A1:2011 |
| Mean modulus of elasticity parallel | 11 kN/mm ² | |
| Natural durability | Durability class 2 | |
| Reaction to fire | D-s2, d0 | |
| | | |

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Mr Ville Kopra, Managing Director At Heinola on 24th September 2014

f out